



Part# BRC520

Congratulations on your purchase of an ASV C/5 Sport Streetbike lever. The correct installation of control levers on a sport/street motorcycle is critical. Incorrect installation or the installation of an incorrect part can result in a malfunction of your clutch and / or front brake system. This lever should be installed by a certified mechanic; preferably at your local motorcycle dealer service dept. ASV Inventions, Inc. accepts no liability for malfunctions as a result of incorrect installation or the installation of a part that was not designed specifically for your motorcycle. Please check the list below to confirm that the correct year, make and model of your motorcycle is listed. If the correct year, make and model of your motorcycle is *not* listed below, then this part is *not* the correct part for your motorcycle and must *not* be installed onto your motorcycle.

ASV C/5 Sport front brake lever part number: BRC520 fits only the following motorcycles:

Please disregard any dashes or letters after this part number that are listed on the part number label of this box that your lever came in, (ex: BRC520-SK) Any dashes or letters following your part number are for colors and/or length of the lever and do not affect the application of the lever to the bike.

HONDA*	YEAR	PART#
CB599/CB600Hornet	(98-06)	BRC520
CBR600 F2,F3,F4,F4i	(91-06)	BRC520
CB 919	(02-06)	BRC520
CBR 900RR	(93-99)	BRC520
VTR1000F	(98-05)	BRC520
VFR750	(91-97)	BRC520
VF750S Sabre	(82-86)	BRC520
VFR800	(02-07)	BRC520
Magna	(2002)	BRC520

***ALL HONDA APPLICATIONS REQUIRE AN ADDITIONAL BRAKE LIGHT TAB BLOCK TO BE INSTALLED. PLEASE SEE INSTRUCTIONS.**

KAWASAKI	YEAR	PART#
ZX6R	(00-02)	BRC520
ZX6RR	(03-04)	BRC520
ZX636R	(03-04)	BRC520
ZZR600	(05-07)	BRC520
ZX9	(94-97)	BRC520
ZX9R	(00-03)	BRC520
ZX10R	(04-05)	BRC520
ZX12R	(00-05)	BRC520
Z750	(2007)	BRC520
Z1000	(03-06)	BRC520
ZX7R/RR	(89-03)	BRC520
ZRX1100/1200	(99-07)	BRC520
ZX1100/ZX-11	(90-01)	BRC520
ZZR1200	(02-05)	BRC520
ZG1000 Concourse	(92-06)	BRC520

SUZUKI	YEAR	PART#
GSXR 600	(97-03)	BRC520
GSXR 750	(96-03)	BRC520
GSXR 1000	(01-04)	BRC520
TL1000S	(97-01)	BRC520
TL1000R	(98-03)	BRC520
HAYABUSA	(99-07)	BRC520
SV1000/S	(03-07)	BRC520
1200 Bandit	(01-06)	BRC520

SUZUKI	YEAR	PART#
1250 Bandit	(2007)	BRC520
DL1000/V-Strom	(02-07)	BRC520
GSX1400	(01-07)	BRC520
GSF650 Bandit	(2007)	BRC520
SV650/SV650S	(99-06)	BRC520
DL650 V-Strom	(04-07)	BRC520
Katana 600 / 750	(98-06)	BRC520

TRIUMPH	YEAR	PART#
Daytona 955i	(97-03)	BRC520
Speed Triple	(97-03)	BRC520
Sprint RS	(99-03)	BRC520
Sprint ST	(97-03)	BRC520
TT 600	(00-03)	BRC520
Speed Four	(03-04)	BRC520
Speed Four	(05-06)	BRC520
Speed Triple	(04-07)	BRC520
Daytona 600/650	(04-05)	BRC520
Daytona 955i	(04-06)	BRC520
Sprint ST/RS	(04-07)	BRC520
Thrupton	(04-07)	BRC520
Bonneville T100	(06-07)	BRC520
Tiger	(2007)	BRC520
Rocket III	(04-07)	BRC520

YAMAHA	YEAR	PART#
R6	(99-04)	BRC520
FZ1	(01-05)	BRC520
R1	(02-03)	BRC520
R6S(USA version)	(06-07)	BRC520
R6S (Canadian)	(2007)	BRC520

If your motorcycle is not on this list, this part # BRC520 is not the correct part for your Motorcycle.

For any questions regarding correct application for your motorcycle, please call ASV Inventions, Inc., toll free, at:


1-877-278-7000

PLEASE SEE OTHER SIDE FOR DETAILED INSTALLATION INSTRUCTIONS

INSTALLATION INSTRUCTIONS FOR PART # BRC520

Tools and supplies needed: 1) 10mm wrench or socket, 1 large flat-blade screwdriver, 1 small phillips head screwdriver, cleaning rag, lightweight grease.

1 To remove your stock lever, use a 10mm wrench or socket to remove the locknut attached to the main pivot bolt that holds the lever. Once the locknut is removed, unscrew the main pivot bolt with a large flat-blade screwdriver. After the pivot bolt is removed, the lever will detach from the master cylinder.



2 FOR HONDA MOTORCYCLES ONLY- You must install a small Tab Block to the brake light switch as shown on photo #3 This will allow your rear brake light to function properly. The Block and screw that holds it on are in a small plastic bag marked "HONDA BRAKE LIGHT TAB".



3 Clean the area where your stock lever was with a clean rag, removing all dirt, dust and debris. Add a small dab of grease to the end of your new ASV lever where it contacts the plunger on the master cylinder. This is important to allow the two contact points to work smoothly together until they are properly worn in.



4 Place the lever into the master cylinder as shown. Install the main pivot bolt, and tighten it until it is snug against the master cylinder. Do not over-tighten, as it could cause the lever to bind in the master cylinder.



5 Install the locknut onto the main pivot bolt and tighten. Use the flat-blade screwdriver to keep the main pivot bolt from turning while tightening the locknut. Do not over tighten the locknut as it can cause binding of the lever and master cylinder. Maximum torque on locknut should be five (5) foot-lbs. or sixty (60) inch-lbs.



After installation is complete, with the engine off and bike out of gear, apply the front brake several times to ensure it is functioning properly. There should be no drag and the front wheel should spin freely when brake is not engaged. If something does not seem right, consult your mechanic or contact ASV technical support before riding your motorcycle.

IMPORTANT: Do not ride your motorcycle if there is any drag or the front wheel does not spin freely after installation.